

Sensor Solutions for Mobile Lift Applications



> Telemecanique Sensors

Simply easy!

Simplicity



Proximity



Expertise



Telemecanique Sensors is a world-class global brand offering a comprehensive line of products with over 25,000 types of sensors, including limit switches, pressure sensors, photoelectric sensors and proximity sensors. In addition, we provide state-of-the-art RFID systems that are compatible with many PLC manufacturers.

Telemecanique Sensors has all the right agency approvals, such as UL, IEC, NEMA, CE, CCC, UL, CSA, and EAC.

Telemecanique Sensors is focused on three core values — Simplicity, Proximity, and Expertise. We have become experts in factory automation sensors as well as specialists in demanding applications, making our customers' lives "Simply easy!"

> Innovation focus



The new, software-configurable XXW54 Wide Beam Ultrasonic Sensor is a highly effective way to avoid mobile equipment collisions, both on the ground and when boom or scissor lift platforms rise into the air. The newly designed PCB of the sensor expands the width of the detection beam so it can cover a greater area.

Detection over a large coverage area



- Emits a beam with a 50° angle up to 1.5 meters.
- When conditions require multiple sensors installed in close proximity to each other, the 'synchronization' feature of the new XX Ultrasonic sensors allows reliable detection of objects from each sensor with minimal risk of cross-talk.



Detection of obstacles in harsh environments




- Anti-UV plastic housing allows operation in temperatures ranging from -40° C to +70° C.

Highly immune to electromagnetic interference



- The new XX Ultrasonic Sensors are E2-certified for mobile equipment. This entails a higher immunity to electromagnetic interference even in the most demanding environments.


> Truck loading cranes



- | | | |
|---|---|--|
| 1 | XCMV or XCMD Limit Switch | Compact body and modular head allows easy mechanical adaptation. |
| 2 | XMEP / XMLR / ZMLP Pressure Sensors / Monitor | Compact and robust for reliable operation. |
| 3 | XS SIL2 Inductive Sensor | Compact, robust, and increases level of safety. |
| 4 | XCKD Limit Switch & XCKZ05 Accessory | Robust for increased resistance to the operating environment. |
| 5 | XS Inductive Sensor | Easy installation and adjustment. |




> Garbage Trucks




- 1 XUSL Light Curtains Compact and robust for reliable operation.
- 2 XU2S Photoelectric Sensor High levels of reliability and quality as well as long life duration.
- 3 6 XG RFID Systems Open for a free choice of electronic tags and networks.
- 4 XMEP Pressure Transmitter Easy installation and adjustment.
- 5 7 XS Inductive Sensors Simple set-up and maintenance.
- 8 XX Ultrasonic Sensors E2-certified for Mobile Equipment with better immunity against EMC interference.




> Scissor Lift Platforms



- 1 XCMD Limit Switch & XCMZ06 Accessory Compact and multitrack mounting for detecting the various heights.
- 2 XMEP Pressure Sensor Compact and robust for reliable operation.
- 3 XCMV or XCKP Limit Switch Compact, providing easy mechanical adaptation.
- 4 XXW54 Wide Beam Ultrasonic Sensors E-certified with better immunity against EMC interference and a larger beam width.




> Boom Lift Platforms



- 1 4 XCKP or XCMD Limit Switch Compact body and modular head allows easy mechanical adaptation.
- 2 XCKP Limit Switch Compact, providing easy mechanical adaptation.
- 3 XXW54 Wide Beam Ultrasonic Sensors E-certified with better immunity against EMC interference and a larger beam width.
- 5 XMEP Pressure Transmitter Compact and robust for reliable operation.
- 6 XS Inductive Sensors Easy installation and adjustment.
- 7 XCMD Limit Switch The most compact Limit Switch body on the market with integrated connectors.



> Fork Lifts



- 1 XCKP or XCMD Limit Switch Compact body and modular head allows easy mechanical adaptation.
- 2 XCMV Limit Switch The most compact Limit Switch body on the market with integrated connectors.
- 3 XCMD Limit Switch Compact body and a wide variety of heads for easier integration.
- 4 XMEP Pressure Sensor Compact and robust for reliable operation.
- 5 XS Inductive Sensor Easy installation and adjustment.
- 6 XXW54 Wide Beam Ultrasonic Sensors E-certified with better immunity against EMC interference and a larger beam width.



> Choose product best-suited for your application

Limit switches

Product	Contact	Connection	Connection			Product	Connection			
			NO+NC Snap	NO+NC Slow	AMP 4P Connector		Deutsch DT04 4P Connector			
XCKD Metal	NO+NC Snap	1/2 NPT	XCKD2110N12	XCKD2102N12	XCKD2118N12	XCMD	AMP 4P Connector	Plunger	XCMD2110AM4	XCMD2510AM4
		M16	XCKD2110P16	XCKD2102P16	XCKD2118P16			Roller plunger	XCMD2102AM4	XCMD2502AM4
		Pg11	XCKD2110G11	XCKD2102G11	XCKD2118G11			Plastic roller lever	XCMD2115AM4	XCMD2515AM4
XCKP Plastic	NO+NC Snap	1/2 NPT	XCKP2110N12	XCKP2102N12	XCKP2118N12	XCMV	Deutsch DT04 4P Connector	Plunger	XCMV2110D44	XCMV2510D44
		M16	XCKP2110P16	XCKP2102P16	XCKP2118P16			Roller plunger	XCMV2102D44	XCMV2502D44
		Deutsch	XCKP2110D44	XCKP2102D44	XCKP2118D44			Plastic roller lever	XCMV2115D44	XCMV2515D44
XCKT Plastic	NO+NC Snap	1/2 NPT	XCKT2110N12	XCKT2102N12	XCKT2118N12	XCMV	M12 Connector	Plunger	XCMV2110M12	XCMV2510M12
		M16	XCKT2110P16	XCKT2102P16	XCKT2118P16			Roller plunger	XCMV2102M12	XCMV2502M12
		Pg11	XCKT2110G11	XCKT2102G11	XCKT2118G11			Plastic roller lever	XCMV2115M12	XCMV2515M12
XCMD Metal	NO+NC Snap NO+NC Slow	1 m	XCMD2110L1	XCMD2102L1	XCMD2115L1	XCMD	AMP 4P Connector	Plunger	XCMD2110M12	XCMD2510M12
		1 m	XCMD2510L1	XCMD2502L1	XCMD2515L1			Roller plunger	XCMD2102M12	XCMD2502M12

Inductive sensors

Product	Sensing distance	Sensing distance					Product	Sensing distance	
		4 mm	8 mm	5 mm	10 mm	15 mm		4 mm	8 mm
XS	cable	XS112B3PAL2	XS118B3PAL2	XS7F1A1PAL2	XS7E1A1PAL2	XS7C1A1PAL2	DC 3 wires NO+NC	XS112B3PCL2	XS118B3PCL2
		XS112B3PAM12	XS118B3PAM12	XS7F1A1PAL01M8	XS7E1A1PAM8	XS7C1A1PAM8		XS112B3PCM12	XS118B3PCM12
NPN	connector	XS112B3NAL2	XS118B3NAL2	XS7F1A1NAL2	XS7E1A1NAL2	XS7C1A1NAL2	E2 CERTIFIED	XS112B3NAM12	XS118B3NAM12
		XS112B3NAM12	XS118B3NAM12	XS7F1A1NAL01M8	XS7E1A1NAM8	XS7C1A1NAM8			

Pressure transmitters

Product	Connector	Analogue output	Pressure range					Product	Output
			0...60 bar	0...100 bar	0...250 bar	0...400 bar	0...600 bar		
XMPE	M12	0,5-4, 5V	XMPE060BD11F	XMPE100BD11F	XMPE250BD11F	XMPE400BD11F	XMPE600BD11F	Display for XMPE	PNP 2 switching outputs ZMLPA2P0SH
		4-20mA	XMPE060BD21F	XMPE100BD21F	XMPE250BD21F	XMPE400BD21F	XMPE600BD21F		
		0-10V	XMPE060BD71F	XMPE100BD71F	XMPE250BD71F	XMPE400BD71F	XMPE600BD71F		
XMPE	Deutsch DT04-3P	0,5-4, 5V	XMPE060BT11F	XMPE100BT11F	XMPE250BT11F	XMPE400BT11F	XMPE600BT11F	PNP Analogue 4...20mA + 1 switching output ZMLPA2P0SH	
		4-20mA	XMPE060BT21F	XMPE100BT21F	XMPE250BT21F	XMPE400BT21F	XMPE600BT21F		
		0-10V	XMPE060BT71F	XMPE100BT71F	XMPE250BT71F	XMPE400BT71F	XMPE600BT71F		
XMPE	AMP Superseal 1,5 3-pin	0,5-4, 5V	XMPE060BV11F	XMPE100BV11F	XMPE250BV11F	XMPE400BV11F	XMPE600BV11F	PNP Analogue 4...20mA + 1 switching output ZMLPA2P0SH	
		4-20mA	XMPE060BV21F	XMPE100BV21F	XMPE250BV21F	XMPE400BV21F	XMPE600BV21F		
		0-10V	XMPE060BV71F	XMPE100BV71F	XMPE250BV71F	XMPE400BV71F	XMPE600BV71F		
XMLR	2 switching outputs	Analogue 4...20mA + 1 switching output	0...100 bar	0...160 bar	0...250 bar	0...400 bar	0...600 bar	ZMLPA2P0SH	
			XMLR100M2P05	XMLR160M2P05	XMLR250M2P05	XMLR400M2P05	XMLR600M2P05		
XMLR	2 switching outputs	Analogue 4...20mA + 1 switching output	0...100 bar	0...160 bar	0...250 bar	0...400 bar	0...600 bar	ZMLPA2P0SH	
			XMLR100M1P05	XMLR160M1P05	XMLR250M1P05	XMLR400M1P05	XMLR600M1P05		

Ultrasonic Sensors

Product	Sensing Distance	Analogue Output	Digital output	Connection		Reference Number
				0.15 cable + 6-pin Deutsch male connector	0.5M cable	
XXW54P3HPL01DM6	3m	0,5 - 4,5 V	PNP	0.15 cable + 6-pin Deutsch male connector	0.5M cable	XXW54P3HPL05
	1m Adjustable	n/a	PNP	5-pin M12 male connector		XXS18S1PM12
XXS18S1AM12	1m Adjustable	4-20mA	n/a	5-pin M12 male connector		XXS18S1AM12

Discover our complete offer: www.telemecaniquesensors.com or contact your local sales agency

TMSS France SAS

Share capital: 366 931 214 euros
2 Avenue Gambetta - Tour Eqho
92400 Courbevoie
908 125 255 RCS de Nanterre
www.telemecaniquesensors.com

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. As standards, specifications and design change from time to time, please ask for confirmation of the information given in this publication. Neither TMSS France nor any of its subsidiaries or other affiliated companies shall be responsible or liable for misuse of the information contained in this document.

Telemecanique™ Sensors is a trademark of Schneider Electric Industries SAS used under license by TMSS France. Any other brands or trademarks referred to in this document are property of TMSS France or, as the case may be, of its subsidiaries or other affiliated companies. All other brands are trademarks of their respective owners.

As standards, specifications and design change from time to time, please ask for confirmation of the information given in this publication